
RF Cavity Combiners 800-2500MHz From <http://www.jammerbooster.com/>

MODEL:	KC-2GD/2GW/2DW/3GDW
SIZE:	152*94*33
PACKAGE:	Neutral packing

RF Cavity Combiners 800-2500MHz

Features:

Low insertion loss, high isolation, reliable, suitable for the microwave mobile communication system.

Specific parameters can be designed according to user's requirements.

Applications:

Mobile Communication Network Optimization and In-door distribution system.

Technical Specifications

Items	GSM+DCS	GSM+WCDMA	DCS+WCDMA	GSM+DCS+WCDMA
Model NO.	KC-2GD	KC-2GW	KC-2DW	KC-3GDW
Frequency Range (MHz)	available upon request			
Insertion Loss(dB)	0.3	0.3	0.8	0.4/0.8/0.8
Isolation(dB)	?80	?90	?80	?80
Inter-modulation	?140dBc(+43dBm*2)			
V.S.W.R	?1.25			
Impedance (?)	50			

Power Handling(W)	100			
RF Connector	N-Female			
Operating Temperature	-35 °C~+60 °C			
Dimension (mm)	152*94*33	152x94*32	176*142*42	210*142*42
Weight(Kg)	0.8	0.78	1.2	1.4
Housing material	Aluminum Alloy			



